



Europäisches Patentamt
European Patent Office
Office européen des brevets



Publication number: **0 596 200 A2**

EUROPEAN PATENT APPLICATION **BEST AVAILABLE COPY**

Application number: **93111177.7**

Int. Cl.⁵: **H04L 12/56, H04Q 11/04**

Date of filing: **13.07.93**

Priority: **06.11.92 GB 9223254**

Date of publication of application:
11.05.94 Bulletin 94/19

Designated Contracting States:
AT BE CH DE ES FR GB IT LI NL SE

Applicant: **ROKE MANOR RESEARCH LIMITED**
Roke Manor
Romsey, Hampshire, SO51 0ZN(GB)

Inventor: **Hayter, Andrew Timothy**
3 Cobden Gardens
Bitterne Park, Southampton SO2 4LN(GB)
Inventor: **Stewart, Ian Bernard**
4 Fielden Close
North Baddesley, Hampshire SO52 9ND(GB)

Inventor: **Worster, Thomas**
Belgrad Strasse 24
D-8000 München 40(DE)
Inventor: **Davis, Simon Paul**
17 Westering
Romsey, Hampshire SO51 7LX(GB)
Inventor: **Fischer, Wolfgang**
Erikastrasse 18d
D-8034 Germersing(DE)

Representative: **Allen, Derek**
Siemens Group Services Limited
Intellectual Property Department
Roke Manor
Old Salisbury Lane
Romsey Hampshire SO51 0ZN (GB)

Improvements in to ATM signal processors.

An ATM signal processor system for processing ATM data cells which in combination define a data package wherein the last cell of a package is characterised by an identifying code, comprising means for multiplexing the cells of different data packages thereby to provide a serial data stream, a server, a buffer store via which the server is fed with the serial data stream, the buffer store having a threshold capacity beyond which cells are discarded, and dis-

carded cell identifier/rejecter means which serves to identify and store the identity of a data package with which a discarded cell is associated, so as to be set thereafter to reject subsequently received cells with the same data package identity, until being reset consequent upon receipt of the last cell of the said package as indicated by its characteristic identifying code.




Fig.1

This invention relates to asynchronous transfer mode (ATM) signal processor systems and more especially it relates to such systems for ATM data transmission, wherein the transmission comprises a number of cells which are transmitted successively and which in combination define a data package or frame wherein the last cell of the package is characterised by an identifying data code.

When a plurality of transmissions are made each relating to a different data package, the cells of the various transmissions are multiplexed or interleaved to provide a serial data stream. It will be appreciated that ATM data traffic is inherently bursty in nature and in order to accommodate widely varying data rates arriving at a server, a serial buffer store is normally provided via which the server is fed with the serial data stream. Since in times of heavy traffic the capacity of the buffer store may be inadequate, the buffer store is arranged to have an in-built threshold capacity beyond which data is discarded and lost whereby retransmission is required.

It will be appreciated that when a cell is discarded, the data package of which it forms a part is corrupted such that subsequently transmitted cells which form part of the same data package are useless. As the buffer store empties however, useless subsequently received cells relating to the corrupted data package may nevertheless be stored in the buffer so as to occupy buffer storage capacity which might be more fruitfully used whereby data transmission efficiency is reduced.

It is an object of the present invention to provide an ATM signal processor system, wherein the cells of data packages corrupted as aforesaid are not needlessly stored whereby system efficiency is improved.

According to the present invention an ATM signal processor system for processing ATM data cells which in combination define a data package wherein the last cell of a package is characterised by an identifying code, comprises means for multiplexing the cells of different data packages thereby to provide a serial data stream, a server, a buffer store via which the server is fed with the serial data stream, the buffer store having a threshold capacity beyond which cells are discarded, and discarded cell identifier/rejecter means which serves to identify and store the identity of a data package with which a discarded cell is associated, so as to be set thereafter to reject subsequently received cells with the same data package identity, until being reset consequent upon receipt of the last cell of the said package as indicated by its characteristic identifying code.

The discarded cell identifier/rejecter may comprise address register means in which the address of discarded cells is stored and inhibitor means

responsive to the address of subsequently received cells for deleting them if their address corresponds to an address in the said register, an address being deleted from the register, consequent upon reception of a cell having that address, and additionally being identified as a last cell in a data package by its characteristic identifying code.

The address register means may comprise a mask register.

One embodiment of the invention will now be described by way of example only with reference to the accompanying drawing.

Referring now to the drawing, cell streams relating to data packages F1, F2, F3 and F4 are fed through a multiplexer 1 to provide a serial data stream 2. Each data package may comprise a number of cells, the final cell only of which is identified as such by a characteristic code final cell 3 as shown schematically in the drawing.

The multiplexed serial cell stream is fed to a buffer 4 including a threshold capacity 5 beyond which cells are discarded. The addresses of discarded cells are stored in a discard mask store register 6 which comprises a plurality of mask address stores for storing addresses appertaining to a number of different cells. When the address of a discarded cell has been stored, subsequently received cells are examined and details of their address are fed over the lines 7 to the discard mask store register 6 and if correspondence obtains between the address of an incoming cell and an address stored therein, that incoming cell is deleted. In the event that a cell arrives having an address which corresponds to one of the addresses stored in the register 6 and additionally is identified by a characteristic code as a last cell 3 of a data package then the discard mask address store appertaining thereto is emptied so as to be available to receive the address of a newly discarded cell.

It will be appreciated that once a cell has been deleted due to buffer overflow, when the threshold has been reached, (which is the most common cause of cell loss), the rest of the cells which form part of the same frame or data package will also be deleted without increasing frame loss, whereby optimum use of the buffer store for wanted cells is facilitated. Thus by deleting all cells making up a particular frame in conditions of high buffer usage, the continuing deletion of specific cells making up a frame even after the buffer usage has dropped below threshold T, will reduce the chance of other frames being deleted.

Various modifications may be made to the arrangements shown without departing from the scope of the invention and for example any suitable address identifying/storage/discard means may be used as will be well known to those skilled

in the art.

Claims

1. An ATM signal processor system for processing ATM data cells which in combination define a data package wherein the last cell of a package is characterised by an identifying code, comprising means for multiplexing the cells of different data packages thereby to provide a serial data stream, a server, a buffer store via which the server is fed with the serial data stream, the buffer store having a threshold capacity beyond which cells are discarded, and discarded cell identifier/rejecter means which serves to identify and store the identity of a data package with which a discarded cell is associated, so as to be set thereafter to reject subsequently received cells with the same data package identity, until being reset consequent upon receipt of the last cell of the said package as indicated by its characteristic identifying code.
 - 5
 - 10
 - 15
 - 20
2. A system as claimed in claim 1, wherein the discarded cell identifier/rejecter comprises address register means in which the address of discarded cells is stored and inhibitor means responsive to the address of subsequently received cells for deleting them if their address corresponds to an address in the said register, an address being deleted from the register, consequent upon reception of a cell having that address, and additionally being identified as a last cell in a data package by its characteristic identifying code.
 - 25
 - 30
 - 35
3. A system as claimed in claim 2, wherein the address register means comprises a mask register.
 - 40

45

50

55




Fig.1

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 596 200 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
06.05.1998 Bulletin 1998/19

(51) Int. Cl.⁶: H04L 12/56, H04Q 11/04

(43) Date of publication A2:
11.05.1994 Bulletin 1994/19

(21) Application number: 93111177.7

(22) Date of filing: 13.07.1993

(84) Designated Contracting States:
AT BE CH DE ES FR GB IT LI NL SE

(30) Priority: 06.11.1992 GB 9223254

(71) Applicant:
ROKE MANOR RESEARCH LIMITED
Romsey, Hampshire, SO51 0ZN (GB)

(72) Inventors:
• Hayter, Andrew Timothy
Bitterne Park, Southampton SO2 4LN (GB)
• Stewart, Ian Bernard
North Baddesley, Hampshire SO52 9ND (GB)

• Worster, Thomas
D-8000 München 40 (DE)
• Davis, Simon Paul
Romsey, Hampshire SO51 7LX (GB)
• Fischer, Wolfgang
D-8034 Germersing (DE)

(74) Representative: Allen, Derek
Siemens Group Services Limited
Intellectual Property Department
Roke Manor
Old Salisbury Lane
Romsey Hampshire SO51 0ZN (GB)

(54) Improvements in to ATM signal processors

(57) An ATM signal processor system is disclosed for processing ATM data cells which in combination define a data package wherein the last cell of a package is characterised by an identifying code, comprising means for multiplexing the cells of different data packages thereby to provide a serial data stream, a server, a buffer store via which the server is fed with the serial data stream, the buffer store having a threshold capacity beyond which cells are discarded, and discarded cell

identifier/rejecter means which serves to identify and store the identity of a data package with which a discarded cell is associated, so as to be set thereafter to reject subsequently received cells with the same data package identity, until being reset consequent upon receipt of the last cell of the said package as indicated by its characteristic identifying code.




Fig.1

EP 0 596 200 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 93 11 1177

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.C1.5)
X	COOPER C A ET AL: "TOWARD A BROADBAND CONGESTION CONTROL STRATEGY" IEEE NETWORK: THE MAGAZINE OF COMPUTER COMMUNICATIONS, vol. 4, no. 3, May 1990, pages 18-23, XP000160044 * page 18, left-hand column, paragraph 3 *	1	H04L12/56 H04Q11/04
A	* page 19, left-hand column, paragraph 1-3 * * figure 2 * * page 21, right-hand column, paragraph 1-2 *	2.3	
A	TAKEO KOINUMA ET AL: "AN ATM SWITCHING SYSTEM BASED ON A DISTRIBUTED CONTROL ARCHITECTURE" INNOVATIONS IN SWITCHING TECHNOLOGY, STOCKHOLM, MAY 28 - JUNE 1, 1990, vol. 5, 28 May 1990, INSTITUTE OF ELECTRICAL AND ELECTRONICS ENGINEERS, pages 21-26, XP000130921 * sections 4.1, 4.2 and 5 *	1-3	
			TECHNICAL FIELDS SEARCHED (Int.C1.5)
			H04L H04Q
The present search report has been drawn up for all claims			
Place of search		Date of completion of the search	Examiner
THE HAGUE		3 March 1998	Lindner, A
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03 82 (P4/C01)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)

THIS PAGE BLANK (USPTO)